

**Amendments to the Claims:**

This listing of claims will replace all prior versions and listings of claims in the application:

**Listing of Claims:**

1. (Currently Amended) An apparatus for inspecting a film carrier tape for mounting electronic component in which a plurality of electronic component mounting portions is provided in multiple ~~stripes~~ strips in a transverse direction, comprising:

an unwinding device for unwinding the film carrier tape for mounting electronic component in the multiple ~~stripes~~ strips in which the individual film carrier tapes for mounting electronic component previously cut and separated into the individual ~~stripes~~ strips are wound upon an unwinding reel, respectively;

a back tension roller;

an inspecting section for simultaneously inspecting the film carrier tapes for mounting electronic component, which are cut into ~~the stripes~~ strips, while causing them to run in parallel with each other; ~~and~~

a drive gear;

a take-up device for simultaneously taking up the film carrier tapes for mounting electronic component cut into ~~the stripes~~ strips, which are inspected in the inspecting section upon a plurality of take-up reels attached to an identical take-up shaft in parallel, respectively; ~~and~~

wherein the apparatus further comprises a guide member located at the inspection section for causing the cut strips of film carrier tapes to run in parallel with each other, the guide member comprising:

a side guide portion formed on opposed transverse ends of the guide member to guide opposed outermost sides of the parallel running strips of film carrier tapes,

a centrally located adjacent part guide portion positioned intermediate the side guide portions to guide adjacent innermost adjacent sides of the parallel running strips of film carrier tapes,

said guide member further having undercut portions defining underlying spaces beneath each transverse region between each of the outermost side guide portions and the centrally located adjacent part guide portion whereby only edge portions of the adjacent strips are engaged by the guide member and the underlying spaces do not contact a central region of the strips running parallel through the guide member, whereby interaction between the edge support provided by the guide member and the drive gear and the back tension roller eliminates a transverse curling of the strips and causes the strips of film carrier tapes to reside in a common plane so as to locate an entire transverse width of the strips in a common focal length for simultaneous viewing of the strips in the inspecting station.

2. (Currently Amended) An apparatus for inspecting a film carrier tape for mounting electronic component in which a plurality of electronic component mounting portions is provided in multiple ~~stripes~~ strips in a transverse direction, comprising:

an unwinding device for unwinding the film carrier tape for mounting electronic component in the multiple ~~stripes~~ strips in which the individual film carrier tapes for mounting electronic component previously cut into ~~the stripes~~ strips are wound upon an unwinding reel, respectively;

a back tension roller;

an inspecting section for simultaneously inspecting the film carrier tapes for mounting electronic component, which are cut into ~~the stripes~~ strips, while causing them to run in parallel with each other; and

a drive gear;

a take-up device for simultaneously taking up the film carrier tapes for mounting electronic component cut into ~~the stripes~~ strips, which are inspected in the

**Response Under 37 CFR 1.116**

**Expedited Procedure**

**Examining Group 1734**

Appl. No. 10/783,114

Amdt. dated July 24, 2006

Reply to Office Action of March 24, 2006

Attorney Docket No. 1217-040374

inspecting section, upon a plurality of take-up reels attached to separate take-up shafts in parallel, respectively; and

wherein the apparatus further comprises a guide member located at the inspection section for causing the cut strips of film carrier tapes to run in parallel with each other, the guide member comprising:

a side guide portion formed on opposed transverse ends of the guide member to guide opposed outermost sides of the parallel running strips of film carrier tapes,

a centrally located adjacent part guide portion positioned intermediate the side guide portions to guide adjacent innermost adjacent sides of the parallel running strips of film carrier tapes,

said guide member further having undercut portions defining underlying spaces beneath each transverse region between each of the outermost side guide portions and the centrally located adjacent part guide portion whereby only edge portions of the adjacent strips are engaged by the guide member and the underlying spaces do not contact a central region of the strips running parallel through the guide member, whereby interaction between the edge support provided by the guide member and the drive gear and the back tension roller eliminates a transverse curling of the strips and causes the strips of film carrier tapes to reside in a common plane so as to locate an entire transverse width of the strips in a common focal length for simultaneous viewing of the strips in the inspecting station.

3. (Currently Amended) An apparatus for inspecting a film carrier tape for mounting electronic component in which a plurality of electronic component mounting portions is provided in multiple ~~stripes~~ strips in a transverse direction, comprising:

an unwinding device for unwinding the film carrier tape for mounting electronic component in the multiple ~~stripes~~ strips which are wound upon an unwinding reel;

a slit device for cutting the film carrier tapes for mounting electronic component in the multiple ~~stripes~~ strips, which are unwound from the unwinding

**Response Under 37 CFR 1.116**

**Expedited Procedure**

**Examining Group 1734**

Appl. No. 10/783,114

Amdt. dated July 24, 2006

Reply to Office Action of March 24, 2006

Attorney Docket No. 1217-040374

device, into individual film carrier tapes for mounting electronic component in ~~stripes~~ strips;

a back tension roller;

an inspecting section for causing the film carrier tapes for mounting electronic component, which are cut into the ~~stripes~~ strips by the slit device, to run in parallel with each other and simultaneously inspecting them; ~~and~~

a drive gear;

a take-up device for simultaneously taking up the film carrier tapes for mounting electronic component cut into the ~~stripes~~ strips, which are inspected in the inspecting section, upon a plurality of take-up reels attached to an identical take-up shaft in parallel, respectively; and

wherein the apparatus further comprises a guide member located at the inspection section for causing the cut strips of film carrier tapes to run in parallel with each other, the guide member comprising:

a side guide portion formed on opposed transverse ends of the guide member to guide opposed outermost sides of the parallel running strips of film carrier tapes,

a centrally located adjacent part guide portion positioned intermediate the side guide portions to guide adjacent innermost adjacent sides of the parallel running strips of film carrier tapes,

said guide member further having undercut portions defining underlying spaces beneath each transverse region between each of the outermost side guide portions and the centrally located adjacent part guide portion whereby only edge portions of the adjacent strips are engaged by the guide member and the underlying spaces do not contact a central region of the strips running parallel through the guide member, whereby interaction between the edge support provided by the guide member and the drive gear and the back tension roller eliminates a transverse curling of the strips and causes the strips of film carrier tapes to reside in a common plane so as to locate an entire transverse width of the strips in a common focal length for simultaneous viewing of the strips in the inspecting station.

**Response Under 37 CFR 1.116**

**Expedited Procedure**

**Examining Group 1734**

Appl. No. 10/783,114

Amdt. dated July 24, 2006

Reply to Office Action of March 24, 2006

Attorney Docket No. 1217-040374

4. (Currently Amended) An apparatus for inspecting a film carrier tape for mounting electronic component in which a plurality of electronic component mounting portions is provided in multiple ~~stripes~~ strips in a transverse direction, comprising:

an unwinding device for unwinding the film carrier tape for mounting electronic component in the multiple ~~stripes~~ strips which are wound upon an unwinding reel;

a slit device for cutting the film carrier tapes for mounting electronic component in the multiple ~~stripes~~ strips, which are unwound from the unwinding device, into individual film carrier tapes for mounting electronic component in ~~stripes~~ strips;

a back tension roller;

an inspecting section for causing the film carrier tapes for mounting electronic component, which are cut into ~~the stripes~~ strips by the slit device, to run in parallel with each other and simultaneously inspecting them; ~~and~~

a drive gear;

a take-up device for simultaneously taking up the film carrier tapes for mounting electronic component cut into ~~the stripes~~ strips, which are inspected in the inspecting section, upon a plurality of take-up reels attached to separate take-up shafts in parallel, respectively; ~~and~~

wherein the apparatus further comprises a guide member located at the inspection section for causing the cut strips of film carrier tapes to run in parallel with each other, the guide member comprising:

a side guide portion formed on opposed transverse ends of the guide member to guide opposed outermost sides of the parallel running strips of film carrier tapes,

a centrally located adjacent part guide portion positioned intermediate the side guide portions to guide adjacent innermost adjacent sides of the parallel running strips of film carrier tapes,

said guide member further having undercut portions defining underlying spaces beneath each transverse region between each of the outermost side guide portions and the centrally located adjacent part guide portion whereby only edge

**Response Under 37 CFR 1.116**

**Expedited Procedure**

**Examining Group 1734**

Appl. No. 10/783,114

Amdt. dated July 24, 2006

Reply to Office Action of March 24, 2006

Attorney Docket No. 1217-040374

portions of the adjacent strips are engaged by the guide member and the underlying spaces do not contact a central region of the strips running parallel through the guide member, whereby interaction between the edge support provided by the guide member and the drive gear and the back tension roller eliminates a transverse curling of the strips and causes the strips of film carrier tapes to reside in a common plane so as to locate an entire transverse width of the strips in a common focal length for simultaneous viewing of the strips in the inspecting station.

5. (Canceled)

6. (Currently Amended) The apparatus for inspecting a film carrier tape for mounting electronic component according to ~~claim 1~~ claim 4, further comprising ~~a drive gear for conveying the film carrier tapes for mounting electronic component, which are unwound from the unwinding device and cut into the stripes by the slit device, while causing them to run in parallel with each other, wherein the drive gear including~~ includes:

a both end gear mated with a sprocket hole in side portions on both ends of the film carrier tape for mounting electronic component on the outermost side; and

an intermediate gear mated with a sprocket hole provided in the adjacent side portions of the film carrier tape for mounting electronic component cut into ~~the stripes~~ strips between the both end gears.

7. (Currently Amended) The apparatus for inspecting a film carrier tape for mounting electronic component according to claim 6, further comprising a guide roller,

the guide roller including:

a side guide protruded portion on both ends which serves to guide both end side portions of the film carrier tape for mounting electronic component on the outermost side; and

an adjacent part guide protruded portion protruded to separate and guide adjacent side portions of the film carrier tapes for mounting electronic component cut into the ~~stripes~~ strips between the side guide protruded portions on the both ends.

8. (Currently Amended) The apparatus for inspecting a film carrier tape for mounting electronic component according to ~~claim 4~~ claim 4, wherein a plurality of take-up reels, which are attached to the identical take-up shaft of the take-up device in parallel with each other, are fixed into through holes provided in the vicinity of centers of the reels by means of removable engaging bar members.

9. (Currently Amended) The apparatus for inspecting a film carrier tape for mounting electronic component according to ~~claim 2~~ claim 4, wherein a plurality of take-up reels, which are attached to the separate take-up shafts of the take-up device in parallel with each other, are fixed into through holes provided in the vicinity of centers of the reels by means of removable engaging bar members, respectively.

10. (Currently Amended) The apparatus for inspecting a film carrier tape for mounting electronic component according to ~~claim 4~~ claim 4, wherein the identical take-up shaft of the take-up device is constituted by an air shaft capable of expanding to increase a diameter thereof upon receipt of supply of air, and  
a plurality of take-up reels attached to the take-up shaft in parallel with each other is thus fixed to each other.

11. (Previously Presented) The apparatus for inspecting a film carrier tape for mounting electronic component according to claim 2, wherein the separate take-up shafts of the take-up device are constituted by an air shaft capable of expanding to increase a diameter thereof upon receipt of supply of air, and

a plurality of take-up reels attached to the take-up shaft in parallel with each other is thus fixed, respectively.

12. (Currently Amended) The apparatus for inspecting a film carrier tape for mounting electronic component according to ~~claim 1~~ claim 4, wherein the inspecting section includes a magnifying lens device for magnifying the film carrier tape for mounting electronic component in order to carry out an inspection,

the magnifying lens device including a magnifying lens for magnifying, in a total width direction, the film carrier tapes for mounting electronic component, which are cut into ~~the stripes~~ strips and running in parallel with each other.

13. (Currently Amended) The apparatus for inspecting a film carrier tape for mounting electronic component according to ~~claim 1~~ claim 2, wherein the magnifying lens device has a magnification of 1.4 or more at an enlargement ratio of a length.

14. (Currently Amended) The apparatus for inspecting a film carrier tape for mounting electronic component according to ~~claim 1~~ claim 4, wherein separate dancer rollers are provided for the film carrier tapes for mounting electronic component, which are cut into ~~the stripes~~ strips, between the unwinding device and the inspecting section, respectively.

15. (Currently Amended) The apparatus for inspecting a film carrier tape for mounting electronic component according to claim 1, wherein separate dancer rollers are provided for the film carrier tapes for mounting electronic component, which are cut into ~~the stripes~~ strips, between the take-up device and the inspecting section, respectively.

16. (Currently Amended) The apparatus for inspecting a film carrier tape for mounting electronic component according to claim 1 claim 4, wherein an



identical dancer roller is provided for the film carrier tapes for mounting electronic component, which are cut into ~~the stripes~~ strips, between the unwinding device and the inspecting section.

17. (Currently Amended) The apparatus for inspecting a film carrier tape for mounting electronic component according to claim 1, wherein an identical dancer roller is provided for the film carrier tapes for mounting electronic component, which are cut into ~~the stripes~~ strips, between the take-up device and the inspecting section.

18. (Previously Presented) The apparatus for inspecting a film carrier tape for mounting electronic component according to claim 14, further comprising a looseness control device for detecting a position of the dancer roller to control an amount of looseness of the film carrier tape for mounting electronic component.

19. (Currently Amended) The apparatus for inspecting a film carrier tape for mounting electronic component according to claim 18, wherein the looseness control device includes a guide member for separately changing a guide path for the film carrier tape for mounting electronic component in each ~~stripe~~ strip which is to be guided by the dancer roller.

20. (Withdrawn) A method for inspecting a film carrier tape for mounting electronic component in which a plurality of electronic component mounting portions is provided in multiple stripes in a transverse direction, comprising the steps of:

unwinding, from an unwinding device, the film carrier tape for mounting electronic component in the multiple stripes in which the individual film carrier tapes for mounting electronic component previously cut into the stripes are wound upon an unwinding reel, respectively;

simultaneously inspecting the film carrier tapes for mounting electronic component, which are cut into the stripes, in an inspecting section while causing them to run in parallel with each other; and

simultaneously taking up the film carrier tapes for mounting electronic component cut into the stripes, which are inspected in the inspecting section, upon a plurality of take-up reels attached to an identical take-up shaft of a take-up device in parallel, respectively.

21. (Withdrawn) A method for inspecting a film carrier tape for mounting electronic component in which a plurality of electronic component mounting portions is provided in multiple stripes in a transverse direction, comprising the steps of:

unwinding, from an unwinding device, the film carrier tape for mounting electronic component in the multiple stripes in which the individual film carrier tapes for mounting electronic component previously cut into the stripes are wound upon an unwinding reel, respectively;

simultaneously inspecting the film carrier tapes for mounting electronic component, which are cut into the stripes, in an inspecting section while causing them to run in parallel with each other; and

simultaneously taking up the film carrier tapes for mounting electronic component, which are cut into the stripes, which are inspected in the inspecting section, upon a plurality of take-up reels attached to separate take-up shafts of a take-up device in parallel, respectively.

22. (Withdrawn) A method for inspecting a film carrier tape for mounting electronic component in which a plurality of electronic component mounting portions is provided in multiple stripes in a transverse direction, comprising the steps of:

**Response Under 37 CFR 1.116**

**Expedited Procedure**

**Examining Group 1734**

Appl. No. 10/783,114

Amdt. dated July 24, 2006

Reply to Office Action of March 24, 2006

Attorney Docket No. 1217-040374

unwinding, from an unwinding device, the film carrier tapes for mounting electronic component in the multiple stripes which are wound upon an unwinding reel;

cutting the film carrier tapes for mounting electronic component in the multiple stripes, which are unwound from the unwinding device, into individual film carrier tapes for mounting electronic component in stripes by a slit device;

causing the film carrier tapes for mounting electronic component, which are cut into the stripes by the slit device, to run in parallel with each other and simultaneously inspecting them in an inspecting section; and

simultaneously taking up the film carrier tapes for mounting electronic component cut into the stripes which are inspected in the inspecting section, upon a plurality of take-up reels attached to an identical take-up shaft of a take-up device in parallel, respectively.

23. (Withdrawn) A method for inspecting a film carrier tape for mounting electronic component in which a plurality of electronic component mounting portions is provided in multiple stripes in a transverse direction, comprising the steps of:

unwinding, from an unwinding device, the film carrier tape for mounting electronic component in the multiple stripes which are wound upon an unwinding reel;

cutting the film carrier tapes for mounting electronic component in the multiple stripes which are unwound from the unwinding device, into individual film carrier tapes for mounting electronic component in stripes by a slit device;

causing the film carrier tapes for mounting electronic component, which are cut into the stripes by the slit device, to run in parallel with each other and simultaneously inspecting them in an inspecting section; and

simultaneously taking up the film carrier tapes for mounting electronic component cut into the stripes which are inspected in the inspecting section, upon a

plurality of take-up reels attached to separate take-up shafts of a take-up device in parallel, respectively.

24. (Withdrawn) The method for inspecting a film carrier tape for mounting electronic component according to claim 20, wherein the inspecting section includes a guide member for causing film carrier tapes for mounting electronic component, which are cut into stripes, to run in parallel with each other,

the guide member comprising:

a side guide portion on both ends which serves to guide both end side portions of the film carrier tape for mounting electronic component on an outermost side; and

an adjacent part guide portion, which is protruded to guide adjacent side portions of the film carrier tapes for mounting electronic component cut into the stripes between the guide portions on the both ends.

25. (Withdrawn) The method for inspecting a film carrier tape for mounting electronic component according to claim 20, further comprising a drive gear for conveying the film carrier tapes for mounting electronic component, which are unwound from the unwinding device and cut into the stripes by the slit device, while causing them to run in parallel with each other,

the drive gear including:

a both end gear mated with a sprocket hole in side portions on both ends of the film carrier tape for mounting electronic component on the outermost side; and

an intermediate gear mated with a sprocket hole provided in the adjacent side portions of the film carrier tape for mounting electronic component cut into the stripes between the both end gears.

26. (Withdrawn) The method for inspecting a film carrier tape for mounting electronic component according to claim 25, further comprising a guide roller,

the guide roller including:

a side guide protruded portion on both ends which serves to guide both end side portions of the film carrier tape for mounting electronic component on an outermost side; and

an adjacent part guide protruded portion protruded to separate and guide adjacent side portions of the film carrier tapes for mounting electronic component cut into the stripes between the side guide protruded portions on the both ends.

27. (Withdrawn) The method for inspecting a film carrier tape for mounting electronic component according to any of claim 20, wherein a plurality of take-up reels, which are attached to the identical take-up shaft of the take-up device in parallel with each other, are fixed into through holes provided in the vicinity of centers of the reels by means of removable engaging bar members.

28. (Withdrawn) The method for inspecting a film carrier tape for mounting electronic component according to claim 21, wherein a plurality of take-up reels, which are attached to the separate take-up shafts of the take-up device in parallel with each other, are fixed into through holes provided in the vicinity of centers of the reels by means of removable engaging bar members, respectively.

29. (Withdrawn) The method for inspecting a film carrier tape for mounting electronic component according to claim 20, wherein the identical take-up shaft of the take-up device is constituted by an air shaft capable of expanding to increase a diameter thereof upon receipt of supply or air, and

a plurality of take-up reels attached to the take-up shaft in parallel with each other is thus fixed to each other.

30. (Withdrawn) The method for inspecting a film carrier tape for mounting electronic component according to claim 21, wherein the separate take-up

shafts of the take-up device are constituted by an air shaft capable of expanding to increase a diameter thereof upon receipt of supply of air, and

a plurality of take-up reels attached to the take-up shaft in parallel with each other is thus fixed, respectively.

31. (Withdrawn) The method for inspecting a film carrier tape for mounting electronic component according to claim 20, wherein the inspecting section includes an illuminating device for irradiating a light on the film carrier tape for mounting electronic component in order to carry out an inspection,

the illuminating device having two illuminating lamps, which are provided apart from each other and are serving to irradiate a light on an inspecting position from rearward and above to be simultaneously focused with respect to the film carrier tapes for mounting electronic component, which are cut into the stripes and run in parallel with each other.

32. (Withdrawn) The method for inspecting a film carrier tape for mounting electronic component according to any of claim 20, wherein the inspecting section includes a magnifying lens device for magnifying the film carrier tape for mounting electronic component in order to carry out an inspection,

the magnifying lens device including a magnifying lens for magnifying, in a total width direction, the film carrier tapes for mounting electronic component, which are cut into the stripes and running in parallel with each other.

33. (Withdrawn) The method for inspecting a film carrier tape for mounting electronic component according to claim 20, wherein the magnifying lens device has a magnification of 1.4 or more at an enlargement ratio of a length.

34. (Withdrawn) The method for inspecting a film carrier tape for mounting electronic component according to claim 20, wherein separate dancer rollers are provided for the film carrier tapes for mounting electronic component,

which are cut into the stripes, between the unwinding device and the inspecting section.

35. (Withdrawn) The method for inspecting a film carrier tape for mounting electronic component according to claim 20, wherein separate dancer rollers are provided for the film carrier tapes for mounting electronic component, which are cut into the stripes, between the take-up device and the inspecting section.

36. (Withdrawn) The method for inspecting a film carrier tape for mounting electronic component according to claim 20, wherein an identical dancer roller is provided for the film carrier tapes for mounting electronic component, which are cut into the stripes, between the unwinding device and the inspecting section.

37. (Withdrawn) The method for inspecting a film carrier tape for mounting electronic component according to claim 20, wherein an identical dancer roller is provided for the film carrier tapes for mounting electronic component, which are cut into the stripes, between the take-up device and the inspecting section.

38. (Withdrawn) The method for inspecting a film carrier tape for mounting electronic component according to claim 34, further comprising a looseness control device for detecting a position of the dancer roller to control an amount of looseness of the film carrier tape for mounting electronic component.

39. (Withdrawn) The method for inspecting a film carrier tape for mounting electronic component according to claim 38, wherein the looseness control device includes a guide member for separately changing a guide path for the film carrier tape for mounting electronic component in each stripe which is to be guided by the dancer roller.

40. (Currently Amended) The apparatus for inspecting a film carrier tape for mounting electronic component according to claim 2, wherein the inspecting section includes a guide member for causing film carrier tapes for mounting electronic component, which are cut into ~~stripes~~ strips, to run in parallel with each other,

the guide member comprising:

a side guide portion on both ends which serves to guide both end side portions of the film carrier tape for mounting electronic component on an outermost side; and

an adjacent part guide portion, which is protruded to guide adjacent side portions of the film carrier tapes for mounting electronic component cut into ~~the stripes~~ strips between the guide portions on the both ends.

41. (Currently Amended) The apparatus for inspecting a film carrier tape for mounting electronic component according to claim 3, wherein the inspection section includes a guide member for causing film carrier tapes for mounting electronic component, which are cut into ~~stripes~~ strips, to run in parallel with each other,

the guide member comprising:

a side guide portion on both ends which serves to guide both end side portions of the film carrier tape for mounting electronic component on an outermost side; and

an adjacent part guide portion, which is protruded to guide adjacent side portions of the film carrier tapes for mounting electronic component cut into the ~~stripes~~ strips between the guide portions on the both ends.

42. (Currently Amended) The apparatus for inspecting a film carrier tape for mounting electronic component according to claim 4, wherein the inspecting section includes a guide member for causing film carrier tapes for mounting



**Response Under 37 CFR 1.116**

**Expedited Procedure**

**Examining Group 1734**

Appl. No. 10/783,114

Amdt. dated July 24, 2006

Reply to Office Action of March 24, 2006

Attorney Docket No. 1217-040374

electronic component, which are cut into ~~stripes~~ strips, to run in parallel with each other,

the guide member comprising:

a side guide portion on both ends which serves to guide both end side portions of the film carrier tape for mounting electronic component on an outermost side; and

an adjacent part guide portion, which is protruded to guide adjacent side portions of the film carrier tapes for mounting electronic component cut into ~~the stripes~~ strips between the guide portions on the both ends.

43. (Currently Amended) The apparatus for inspecting a film carrier tape for mounting electronic component according to claim 2, further comprising a drive gear for conveying the film carrier tapes for mounting electronic component, which are unwound from the unwinding device and cut into ~~the stripes~~ strips by the slit device, while causing them to run in parallel with each other,

the drive gear including:

a both end gear mated with a sprocket hole in side portions on both ends of the film carrier tape for mounting electronic component on the outermost side; and

an intermediate gear mated with a sprocket hole provided in the adjacent side portions of the film carrier tape for mounting electronic component cut into ~~the stripes~~ strips between the both end gears.

44. (Currently Amended) The apparatus for inspecting a film carrier tape for mounting electronic component according to claim 3, further comprising a drive gear for conveying the film carrier tapes for mounting electronic component, which are unwound from the unwinding device and cut into ~~the stripes~~ strips by the slit device, while causing them to run in parallel with each other,

the drive gear including:

a both end gear mated with a sprocket hole in side portions on both ends of the film carrier tape for mounting electronic component on the outermost side; and

**Response Under 37 CFR 1.116**

**Expedited Procedure**

**Examining Group 1734**

Appl. No. 10/783,114

Amdt. dated July 24, 2006

Reply to Office Action of March 24, 2006

Attorney Docket No. 1217-040374

an intermediate gear mated with a sprocket hole provided in the adjacent side portions of the film carrier tape for mounting electronic component cut into ~~the stripes~~ strips between the both end gears.

45. (Currently Amended) The apparatus for inspecting a film carrier tape for mounting electronic component according to claim 4, further comprising a drive gear for conveying the film carrier tapes for mounting electronic component, which are unwound from the unwinding device and cut into ~~the stripes~~ strips by the slit device, while causing them to run in parallel with each other,

the drive gear including:

a both end gear mated with a sprocket hole in side portions on both ends of the film carrier tape for mounting electronic component on the outermost side; and

an intermediate gear mated with a sprocket hole provided in the adjacent side portions of the film carrier tape for mounting electronic component cut into ~~the stripes~~ strips between the both end gears.

46. (Currently Amended) The apparatus for inspecting a film carrier tape for mounting electronic component according to claim 5, further comprising a drive gear for conveying the film carrier tapes for mounting electronic component, which are unwound from the unwinding device and cut into ~~the stripes~~ strips by the slit device, while causing them to run in parallel with each other,

the drive gear including:

a both end gear mated with a sprocket hole in side portions on both ends of the film carrier tape for mounting electronic component on the outermost side; and

an intermediate gear mated with a sprocket hole provided in the adjacent side portions of the film carrier tape for mounting electronic component cut into ~~the stripes~~ strips between the both end gears.